



DE-MOUNT LT GROUND CARE SPRAYER



For the Groundcare Professional



Standard 300L with 3m boom



De-mount LT

TECHNICAL SPECIFICATIONS



The robust **De-mount LT** sprayer has been designed to fit directly onto the back off the any utility vehicle.

The lowline 300L fiberglass tank enables the operator all-round vision and a list of optional extras makes the unit versatile enough to cope with any grassland-spraying situation.

FEATURES

- Heavy duty tubular steel chassis and spray boom assembly
- Low line fibre glass (GRP) tank giving all-round visibility
- Compact operator friendly design
- Quick coupled easy removable boom system
- Heavy duty high flow pump
- Easily accessible suction filter

Standard Fittings

- 4-section manual spray control c/w manual pressure regulation and boom isolation
- In-cab pump on/off switch box
- 12v heavy duty diaphragm demand pump (26.5 litre)
- Rear folding 3m 6-nozzle boom (detachable)
- Steel tubular section boom with 'break back' end sections
- Colour coded quick fit nozzles with anti-drip check valves
- 15m retractable hose reel and lance kit
- Suction filter

Weight & Dimensions

Weight: 120 Kg (empty)

Length: 1.6m

Width: 1.5m

Height: 0.8m



Optional Extras

- 400L main tank
- 4m or 6m spray boom
- In-cab full electric spray controls
- Electric spray on/off
- Triple nozzle assemblies
- Bout/foam marking system
- Walk-on boom
- Clean water hand wash tank



Leaders in the field of application

Team Sprayers Ltd
Unit 3 Lancaster Way Business Park,
Witchford, Ely, Cambridgeshire CB6 3NW

E sales@team-sprayers.com 

team-sprayers.com • 01353 661211



DEMOUNT PRO

GROUND CARE SPRAYER



Effective, Accurate, Controlled



Shown with 600L tank and electric 6m boom option



Demount Pro

STANDARD FEATURES



Controls

In cab electric spray controls to operate all spray and pressure functions

Work station controlling primary functions to operate the sprayer and when cleaning or filling.

Chemical inductor:

20L hopper for safe transfer of liquids and powders via a high flow venturi system to the main tank, a rotary nozzle for cleaning containers.

Diaphragm pump: PTO driven, high quality Poly Series to withstand any aggressive plant protection chemicals

Clothes storage:
For all PPE equipment.

Clean water supply: 70L supply for tank and boom rinsing.

Booms

Boom construction:

All spray booms are manufactured from steel tubular sections for strength and durability.

Boom height adjustment:

Manual 6-8m; Winch 10 and 12m.

Boom stowage system secures boom assembly in the folded position.

'Break back' boom design is a standard feature on all models to avoid damage from unseen obstructions.

Transport width:

Folds to compact to the following sizes
1.9m [6m model]; 2.4m [12m model]

Large access for tank filling.

Clean water tank rinse

OPTIONAL EXTRAS

Tank options: 400L, 600L, 800L

Boom options: 6M, 7M, 8M, 10M, 12M manual folding or 6 - 8M electric or hydraulic folding.

Dual covered boom system for sensitive areas or windy conditions.

Water suction: enabling tank filling via the main pump.

Walk on boom (lightweight boom system for greens)

Pump hydraulic drive motor kit

Computerised auto spray rate controller automatically adjusts spray application rate to forward speed.

Triple nozzle assemblies

enable the operator to select from a choice of 3 nozzle sizes for various applications.

Other Optional Extras

- Retractable hose reel and hand lance kit
- GPS boom section switching and mapping
- Stainless steel spray lines
- Bout / foam marker
- Hose holder for tank filling
- Upgraded 110Lpm diaphragm pump



Demount Pro

TECHNICAL SPECIFICATIONS

Item	Dimension
Tank capacities [L]	400, 600, 800
Pumps [type / L per min]	Poly 2073 / 73
Boom lengths [m]	4, 6, 7, 8, 10, 12
Weight [Kg]	175 (300L x 6m); 286 (600L x 12m)
Total Height [m]	1.6 [6m]; 2 [12m]
Total Width [m]	1.9 [6m]; 2.4 [12m]



Team Sprayers Ltd
Unit 3 Lancaster Way Business Park,
Witchford, Ely, Cambridgeshire CB6 3NW
E sales@team-sprayers.com 

team-sprayers.com • 01353 661211